

Chapter 14

hertalan easy.stick

hertalan easy.stick is a **hertalan** with a self-adhesive butyl layer. **hertalan** easy.stick is supplied 1.3 and 1.7mm thickness and in widths of 250, 500 and 750mm and in rolls of 20m long.

Application areas

- **hertalan** easy.stick can be used in construction joints between pre-cast concrete panels, joints in steel and stone substrates on wall, floor and ceiling applications.
- **hertalan** easy.stick can also be used for covering gutters, roof edges, and skylight upstands.

Application Methods

hertalan easy.stick can be easily applied to timber, bitumen, concrete steel and stone substrates, the correct procedure is as follows:

1. Ensure the substrate is dry and free of dust and grease.
2. Remove the protective layer from the self-adhesive layer as work proceeds.
3. Roll the membrane with a special silicone roller to ensure optimum adhesion between the self-adhesive bonding layer and the substrate, in cold or damp conditions adhesion can be assisted by warming the material with a hot air gun.
4. A transition joint between two rolls of **hertalan** easy stick should be finished with a strip of **hertalan** fixed with two beads of ks96 and sealed on all edges.

Notes:

- Never make joints of easy.stick to easy.stick, these should always be finished with a strip of hertalan
- Use the hot air gun when the temperature is below 8° and always warm the hertalan side of the material after heating roll the material again with a silicone roller.