

Chapter 15

hertalan S

hertalan S is the collective title for all ***hertalan*** DPC strips. ***hertalan S*** is normally available 0.75, 1.00 and 1.2mm thick and can be supplied 1.5 and 2.0mm thick where required. ***hertalan S*** is available in widths of 100 to 1300mm in rolls 25m long.

Areas of Application

- ***hertalan S*** can be used in all DPC applications, both horizontal and vertical.
- ***hertalan S*** can also be used with ks137 to bridge and waterproof joints in pre-fabricated structures.

Application Method

hertalan S can be fixed to the wall structure using ks96 adhesive sealant, the procedure is as follows:

1. Make sure the substrate is clean and free of dust and grease.
2. Cut off the top 35mm of the cartridge spout at an angle to form a hole of 7mm, apply the ks96 in a 7mm bead, **do not spread the adhesive!**
3. Where the ***hertalan S*** is more than 300mm use 2 beads of ks96.
4. Place the ***hertalan S*** within 5 minutes of applying the beads of ks96.
5. Roll the top of the ***hertalan S*** with a special silicone roller to create a bead of ks96 approximately 25mm wide (50mm where two beads are applied).
6. Checks the spread of ks96 regularly by lifting the seam at regular intervals, after checking ensure that the seam is rolled back properly.
7. A 600ml tube of ks96 will make a seam of 25mm approximately 15m long.